



COCOROSA
SURFACES

RAZZO



OPERA
opus collections



PIEDRA stone collections



MADERA wood collections



OPERA opus collections



FIORA flowery collections



BESPOKE customization

RECREATE THE BEAUTY OF ELEMENTS

Offering sustainable surface solutions with eco-friendly materials developed from the essence of woods, stones and other man-made materials to maintain the beauty as much as the element where the idea was extracted from.





OPERA

opus collections

By definition, an opus is a created work by man, usually of an artistic kind. It is creative and beautiful – a definite work of art to the eye of the beholder.

Cocorosa introduces opus, inspired by man-made materials in the architecture world. Opus tiles provides infinite possibilities to the discerning when it comes to beautiful, modern spaces.

Its range of versatile, neutral hues also aims to delight
The senses.

COCOROSA
SURFACES



100% Waterproof



Antislip Surfaces



Fire Prevention



Stain Resistant



Realistic Finish



Scratch Resistant



High Impact Resistance



LVT GLUE DOWN



LVT CLICK



LVT LOOSE LAY



LVT RIGID CORE



LVT RIGID CORE




LVT RIGID CORE



LVT RIGID CORE

OPERA
RAZZO
Cinder
RAZZO 01



OPERA
RAZZO
Cinder
RAZZO 01



100% Waterproof



Antislip Surfaces



Fire Prevention



Stain Resistant



Realistic Finish



Scratch Resistant



High Impact Resistance



LVT GLUE DOWN



LVT CLICK



LVT LOOSE LAY




LVT REGISTERED CODE



SPC REGISTERED CODE

OPERA
RAZZO
Marone
RAZZO 02




OPERA
RAZZO
Marone
RAZZO 02

OPERA RAZZO
Cinder RAZZO 01



OPERA RAZZO
Marone RAZZO 02

SPECIAL PIECES



SMART SELECT LUXURY VINYL FLOORING LIMITED WARRANTY PERIODS

Thickness	Core	Wear layer	Attached pad	Residential Warranty	L. Commercial Warranty
3.2 mm	Rigid Core	8 mil (0.2mm)	Y / N	10 years	5 years
3.2 mm	Rigid Core	12 mil (0.3mm)	Y / N	15 years	7 years
4 mm	Rigid Core	12 mil (0.3mm)	Y / N	20 years	8 years
5 mm	Rigid Core	20 mil (0.5mm)	Y / N	Limited Lifetime	10 years

Definitions for applications in terms of LVT

RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL
Kitchen	Small restaurant	Large restaurant
Dining room	Small retail shop	Large retail, large office
Bedroom	Waiting rooms	Hair salon (working area)
Bathroom	Trade booths	School classroom
Recreation rooms, foyers	Small Office	Nurses Station

*Residential use, or household conditions means the daily activities commonly associated with residential use.

*Light commercial is defined as environments which do not have heavy commercial traffic, where the flooring is not exposed to a heavy commercial maintenance schedule and where the interior temperature and humidity can be controlled and maintained.

*Commercial is defined as environments which have heavy commercial traffic.

TECHNICAL SPECIFICATIONS

Clasification	Test Standard	Result
Reaction to fire	EN ISO 9239-1	B fl – s1
Impact Insulation Class	ASTM E492-09	52
Sound Transmission Class	ASTM E90-09	54
Determination the content of formaldehyde	ISO 16000-3	A+
Performance	Test Standard	Result
Wear resistance	EN660-1	Group T
Residual indentation after static load	EN436	Pass
Dimensional stability and curling after exposure to heat	EN434	Pass
Flexibility	EN435	Pass
Measurement of dynamic coefficient of friction on dry floor surface	E13893	Pass
Slip resistance	DIN 51130	R10
Resilience to chemicals	EN423	Class 0

FORMATS & RANDOMNESS

LVT Click LVT Sintered Core SPC Rigid Core	INCHES MM FACES	12"X24" 305x610 3	18"X36" * 460X935 2	18"X48" * 460X1220 2	- - -	- - -
LVT Glue Down LVT Loose Lay	INCHES MM FACES	12"X24" 304.8X609.6 3	18"X36" * 457.2X914.4 2	18"X18" 457.2X457.2 4	12"X24" 609.6X609.6 4	36"X36" 914.4X914.4 1

* non-standard formats/size, production upon request/order

email info@cocorosurfaces.com
phone +86 0757 8252 5005

www.cocorosurfaces.com



COCOROSA
SURFACES